

Ohmic and voltage-actived transport of ions through single-walled carbon nanotubes

Vincent Jourdain, Khadija Yazda, Saïd Tahir, Thierry Michel, Bastien Loubet, Manoel Manghi, Jeremy Bentin, Fabien Picaud, John Palmeri, Mohamed El-Amine Kribeche, et al.

▶ To cite this version:

Vincent Jourdain, Khadija Yazda, Saïd Tahir, Thierry Michel, Bastien Loubet, et al.. Ohmic and voltage-actived transport of ions through single-walled carbon nanotubes. NT19, Jul 2019, Wurzburg, Germany. hal-04894925

HAL Id: hal-04894925 https://hal.science/hal-04894925v1

Submitted on 17 Jan 2025

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Ohmic and voltage-actived transport of ions through single-walled carbon nanotubes

<u>Vincent JOURDAIN^a</u>,*_Khadija YAZDA^a, Saïd TAHIR^a, Thierry MICHEL^a, Bastien LOUBET^b, Manoel MANGHI^b, Jeremy BENTIN^c, Fabien PICAUD^c, John PALMERI^a, Mohamed el-Amine Kribeche, ^a Jin Cui, ^a Adrien Noury, ^a François HENN^a

We report studies of ion transport through SWCNTs with diameters of 1.2 to 2 nm showing a linear or, unexpectedly, a voltage-activated I-V dependence [1-3]. Transition from an activated to a linear behavior and stochastic fluctuations between different current levels were notably observed. For linear devices, the high conductance confirmed with different chloride salts indicates that the nanotube/water interface exhibits both a high surface charge density and flow slippage. In addition, the sublinear dependence of the conductance on the salt concentration points toward a charge-regulation mechanism. Theoretical modelling and computer simulations show that the voltage-activated behavior can be accounted for by local energy barriers at the ends of the nanotube. Raman spectroscopy reveals strain fluctuations along the tubes but insufficient doping or variations of doping to account for the apparent surface charge density and energy barriers revealed by ion transport measurements. Chemical moieties at the nanotube mouths are proposed to be responsible for the voltage-activated transport of ions through SWCNTs within this diameter range.

^a Laboratoire Charles Coulomb, CNRS, Univ. Montpellier, Montpellier, France; b Laboratoire de physique théorique (IRSAMC) UMR 5152 CNRS-UPS, Université de Toulouse, France; c Laboratoire de Nanomédecine Imagerie et Thérapeutique (NIT), EA4662 Université de Bourgogne Franche-Comté, UFR ST & CHU Médecine, France e-mail: vincent.jourdain@umontpellier.fr

¹⁾ Yazda et al, MRS Advances, 1(28), 2085.

²⁾ Yazda et al, MRS Advances, 1(28), 2079

³⁾ Yazda et al, Nanoscale (2017), 9, 11976