



HAL
open science

A stepwise uncertainty reduction strategy for the estimation of small quantile sets

Romain Ait Abdelmalek-Lomenech, Julien Bect, Emmanuel Vazquez

► **To cite this version:**

Romain Ait Abdelmalek-Lomenech, Julien Bect, Emmanuel Vazquez. A stepwise uncertainty reduction strategy for the estimation of small quantile sets. MASCOT-NUM 2024, Apr 2024, Hyères, France. hal-04910458

HAL Id: hal-04910458

<https://hal.science/hal-04910458v1>

Submitted on 24 Jan 2025

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution - NonCommercial - NoDerivatives 4.0 International License

A stepwise uncertainty reduction strategy for the estimation of small quantile sets

Romain Ait Abdelmalek-Lomenech^{†,1}, Julien Bect^{‡,1}, Emmanuel Vazquez^{‡,1}

[†] PhD student (presenting author). [‡] PhD supervisor

PhD expected duration: Oct. 2021 – Sep. 2024

¹ Université Paris-Saclay, CNRS, CentraleSupélec, Laboratoire des Signaux et Systèmes,
91190 Gif-sur-Yvette, France

{romain.ait, julien.bect, emmanuel.vazquez}@centralesupelec.fr

Abstract

Given a numerical simulator of a physical phenomenon or system, one often seeks to determine the set of inputs that lead to values with specified properties. Such problems are broadly known as *set inversion* problems.

This communication focuses on a particular robust formulation of such problems that we call *Quantile Set Inversion* (QSI) [1], in which the function of interest has both deterministic and uncertain inputs. In this formulation, given a vector-valued function $f : \mathbb{X} \times \mathbb{S} \mapsto \mathbb{R}^q$, a critical region $C \subset \mathbb{R}^q$, and a threshold $\alpha \in (0, 1)$, the object of interest is the set

$$\Gamma(f) = \{x \in \mathbb{X} : \mathbb{P}(f(x, S) \in C) \leq \alpha\},$$

where \mathbb{X} and \mathbb{S} are respectively the spaces of design and uncertain input variables, and S is a random vector with known probability distribution \mathbb{P}_S .

This object, which we call a *quantile set*, corresponds to the set of deterministic inputs such that the probability (w.r.t. the distribution of the uncertain inputs) that the output variables belong to a critical region is below a threshold. A simple scalar-valued example of such a problem is shown in Figure 1.




Figure 1: Scalar-valued example function (middle), probability density function associated to the distribution \mathbb{P}_S of the uncertain input variable (left), and set of interest obtained with critical region $C = (-\infty, T]$ and threshold $\alpha = 0.025$ (right).

In the case of an *expensive-to-evaluate* function, the objective is to reach a good approximation of the set of interest using only a small, predetermined number of evaluations. The choice of the evaluation points must then be conducted carefully.

To address this set inversion problem, while taking into consideration the expensive-to-evaluate nature of the underlying function, we have proposed a sequential Bayesian strategy [1] based on the *Stepwise Uncertainty Reduction* (SUR) principle (see, e.g., [5] and references therein). Starting from a Gaussian process prior on the unknown function f , the strategy selects the next evaluation points by minimizing the expected future uncertainty about the *quantile set*, measured by a particular metric inspired by [3].

We propose, in this communication, an improvement of the method proposed in [1] to tackle more difficult problems where the quantile set is “small” with respect to the full input domain \mathbb{X} . In particular, we focus on the resolution of two defects arising in such context:

- An adaptive sequential Monte Carlo algorithm is introduced, in the spirit of [4], to tackle the difficulty of the sampling criterion optimization in the case of “small” quantile sets.
- We approach the criterion by using approximated Gaussian process sample paths [2], allowing an improvement in term of computation cost.

The performance of this strategy is illustrated by applying it to several test functions.

Short biography (PhD student)

With a background in probability theory, statistics, machine learning and quantitative finance, Romain Ait Abdelmalek-Lomenech began his PhD in October 2021 with CentraleSupélec, under the supervision of Emmanuel Vazquez and Julien Bect. His work aims at developing new Bayesian methods for the optimization/inversion of expensive-to-evaluate functions in presence of uncertain input variables.

The present work is part of a PhD thesis funded by the French National Research Agency (ANR) in the context of the SAMOURAI project (ANR-20-CE46-0013).

References

- [1] R. Ait Abdelmalek-Lomenech, J. Bect, V. Chabridon, and E. Vazquez. Bayesian sequential design of computer experiments for quantile set inversion. *arXiv preprint arXiv:2211.01008v3*, 2023.
- [2] D. Azzimonti, D. Ginsbourger, C. Chevalier, J. Bect, and Y. Richet. Adaptive design of experiments for conservative estimation of excursion sets. *Technometrics*, 63(1):13–26, 2019.
- [3] J. Bect, D. Ginsbourger, L. Li, V. Picheny, and E. Vazquez. Sequential design of computer experiments for the estimation of a probability of failure. *Statistics and Computing*, 22(3):773–793, 2012.
- [4] J. Bect, L. Li, and E. Vazquez. Bayesian Subset Simulations. *SIAM/ASA Journal on Uncertainty Quantification*, 5:762–786, 2017.
- [5] J. Bect, F. Bachoc, and D. Ginsbourger. A supermartingale approach to Gaussian process based sequential design of experiments. *Bernoulli*, 25(4A):2883–2919, 2019.