



**HAL**  
open science

## Ductility limit predictions for porous materials using a damage coupled CPFEM approach

Shuai Zhou, Mohamed Ben Bettaieb, Farid Abed-Meraim

► **To cite this version:**

Shuai Zhou, Mohamed Ben Bettaieb, Farid Abed-Meraim. Ductility limit predictions for porous materials using a damage coupled CPFEM approach. 19th European Mechanics of Materials Conference (EMMC19), May 2024, Madrid, Spain. <hal-05115311>

**HAL Id: hal-05115311**

**<https://hal.science/hal-05115311v1>**

Submitted on 16 Jun 2025

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire HAL, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



HAL Authorization



# Ductility limit predictions for porous materials using a damage coupled CPFEM approach

**S. Zhou, M. Ben Bettaieb and F. Abed-Meraim**

Université de Lorraine, CNRS, Arts et Métiers Institute of Technology, LEM3, F-57070 Metz, France

Accurate predictions of ductility limits play a crucial role in product design and manufacturing, offering substantial cost reductions in development. In this investigation, attention is focused on the prediction of ductility limits for porous materials. Unlike previous contributions [1,2], we integrate a microscopic damage model based on thermodynamics into the crystal plasticity finite element method (CPFEM) framework in the current study. In this regard, Representative Volume Elements (RVEs) are selected to represent the porous materials at the macroscopic level and an ABAQUS Voronoi Toolbox is developed to generate these RVEs. The macroscopic behavior of these RVEs is determined from that of the constituent single crystals using the periodic homogenization multiscale scheme [1,2,3]. At the single crystal scale, the constitutive equations follow a finite strain rate-independent framework, where the damage variables are defined for each individual slip system. The plastic flow rule is governed by the classical Schmid law. The proposed model is applied to predict the ductility limits for porous materials using the Rice bifurcation criterion. The results show that the damage coupled CPFEM approach accurately predicts the ductility limits, offering valuable tools for optimizing the mechanical properties of advanced materials.

## REFERENCES

- [1] Zhu JC, Ben Bettaieb M, Zhou S, Abed-Meraim F. Ductility limit prediction for polycrystalline aggregates using a CPFEM-based multiscale framework. *Int J Plast* 2023;167:103671.
- [2] Zhu JC, Ben Bettaieb M, Abed-Meraim F, Huang MS, Li ZH. Coupled effects of crystallographic orientation and void shape on ductile failure initiation using a CPFE framework. *Eng Fract Mech* 2023;280:1–21.
- [3] Miehe C, Schröder J, Schotte J. Computational homogenization analysis in finite plasticity simulation of texture development in polycrystalline materials. *Comput Methods Appl Mech Eng* 1999;171:387–418.